

# Comerciales

# Compactos

TEMPERATURA EXTERNA +35°C

TEMPERATURA EXTERNA +45°C

Temp. cámara	+10°C		+5°C		0°C		-5°C		+10°C		+5°C		0°C		-5°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
MSB120T0261F	1163	6,9	1034	5,6	924	4,5	780	3,2	—	—	—	—	—	—	—	—
MSB125N261F	1514	9,2	1335	7,5	1172	5,7	1020	4,2	—	—	—	—	—	—	—	—
MSB125T261F	1698	12	1478	8,9	1291	6,8	1098	4,9	—	—	—	—	—	—	—	—
MSB225N261F	2578	22	2245	17	1868	13	1593	10	2240	16	1926	13	1560	9	1320	6,4
MSB225T38F	2884	26	2529	20	2210	17	1794	12	2574	20	2256	17	1974	14	1549	8,8
MSB135T38F	4950	53	4362	44	3805	36	3265	28	4164	40	3641	32	3148	26	2677	18
MSB235T285F	7726	94	6725	79	5853	65	4940	52	—	—	—	—	—	—	—	—

Temp. cámara	-15°C		-20°C		-25°C		-15°C		-20°C		-25°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
BSB120N0261F	774	2,2	598	1,2	468	0,5	—	—	—	—	—	—
BSB125T261F	1420	7,1	1184	4,7	945	2,7	—	—	—	—	—	—
BSB225T38F	2095	15	1686	10	1314	5,8	1902	12	1494	7,2	1150	3,9
BSB135T38F	2960	24	2456	15	1960	10	2592	17	2146	12	1688	6,3
BSB235T285F	4946	61	4073	44	3251	29	—	—	—	—	—	—

TEMPERATURA EXTERNA +35°C

TEMPERATURA EXTERNA +45°C

Temp. cámara	+10°C		+5°C		0°C		-5°C		+10°C		+5°C		0°C		-5°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
MGM10328F	1055	7,2	910	5,8	779	4,6	652	3,5	906	5,7	779	4,6	664	3,6	553	2,8
MGM10528F	1331	10	1113	7,8	965	6,4	818	5	1161	8,3	965	6,4	833	5,1	702	4
MGM10628F	1455	11	1217	8,9	1062	7,3	903	5,7	1278	9,6	1052	7,2	911	5,8	768	4,6
MGM10728F	1582	13	1416	11	1247	9,2	1075	7,4	1395	11	1247	9,2	1094	7,6	936	5,9
MGM11028F	1802	15	1606	13	1431	11	1236	9,1	1599	13	1421	11	1271	9,5	1092	7,6
MGM21128F	2553	24	2129	19	1843	16	1558	13	2223	20	1843	16	1589	13	1337	10
MGM21229F	2860	29	2506	24	2178	19	1764	15	2520	24	2190	19	1885	15	1521	12
MGM21329F	3113	32	2799	28	2475	23	2149	19	2717	26	2449	23	2162	19	1869	15
MGM31529F	4216	48	3712	41	3221	34	2730	27	3581	39	3150	33	2708	27	2269	21
MGM32029F	4741	55	4149	47	3652	40	3110	32	4070	46	3535	38	3111	32	2621	25

Temp. cámara	-15°C		-20°C		-25°C		-15°C		-20°C		-25°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
BGM11028F	903	4,7	740	3,4	593	2,3	816	4	664	2,8	523	1,9
BGM11228F	1112	6,8	923	4,9	742	3,4	998	5,6	824	4	654	2,7
BGM11728F	1452	11	1186	7,6	920	4,9	1339	9,1	1074	6,4	807	3,9
BGM21828F	1737	14	1423	10	1133	6,9	1569	12	1276	8,5	1001	5,6
BGM22029F	1959	17	1656	13	1346	9,2	1681	13	1205	9,9	1123	6,9
BGM32029F	2632	27	2192	20	1790	15	2189	20	1803	15	1451	10
BGM33029F	3154	32	2650	24	2180	17	2730	26	2280	19	1855	14
BGM34029F	3451	37	2985	30	2519	22	2778	27	2399	20	2020	15

TEMPERATURA EXTERNA +35°C

TEMPERATURA EXTERNA +45°C

Temp. câmara	+10°C		+5°C		0°C		-5°C		+10°C		+5°C		0°C		-5°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
MAS235T485F	7796	102	6786	87	5906	73	4985	60	6716	86	5793	72	5025	60	4186	48
MAS335N485F	10750	149	9345	127	8049	106	6807	87	9308	126	8032	106	6850	88	5747	71
MAS335T485F	12130	172	10665	148	9283	126	7854	103	10522	146	9201	124	7956	105	6670	85
MAS340T485F	15554	230	13627	197	11833	167	10818	140	13359	193	11640	164	10189	140	8577	115

Temp. câmara	-15°C		-20°C		-25°C		-15°C		-20°C		-25°C	
Modelo	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3	Wattios	m3
BAS235T485F	4996	72	4114	55	3283	39	4194	56	3357	40	2608	27
BAS335N485F	7266	122	6092	96	4963	72	6001	94	4982	72	3966	51
BAS335T485F	8135	143	6797	111	5597	85	6788	111	5668	86	4539	63
BAS340T485F	10418	200	8756	158	7195	121	8703	157	7193	121	5809	89

BASE DE CÁLCULO VER PÁGINA 19

techo

compacto

pared

compacto

pared

compacto